

**EUROTROL**®

WATER TREATMENT COMPONENTS



Water softeners

## MWG Manual Water Softeners



- Suitable for residential and commercial water softening applications, as coffee machines, dishwashers, microwave ovens;
- Tank in 304 Stainless Steel;
- They work with mains water pressure;
- They are supplied with and must be operated only with resin approved for drinking water contact use;
- For regeneration use only Sodium Chloride (NaCl) = coarse cooking salt.

### Technical characteristics:

- Nominal Flow Rate at 4 bar = 1.000 l/h
- Operating Water Pressure Range: 1 ÷ 4 bar
- Feed Water Temperature Range: 4 ÷ 25°C
- Room Temperature Range: 4 ÷ 35° C
- Connections: 3/4" G (3/8" G reductions to order separately).

Ref	Description	Fam.	Subfam.	Disp. Stock	
ADD06	MWG MANUAL WATER SOFTENER 6 L	405	805	•	
ADD08	MWG MANUAL WATER SOFTENER 8 L	405	805	•	
ADD12	MWG MANUAL WATER SOFTENER 12 L	405	805	•	
ADD16	MWG MANUAL WATER SOFTENER 16 L	405	805	•	
ADD20	MWG MANUAL WATER SOFTENER 20 L	405	805	•	

Certificates	Manufacturer	Sectors
DM174-2004	<b>MWG</b>	Domestic, Commercial