

EUROTROL®

WATER TREATMENT COMPONENTS



Water softeners



MWG Manual Water Softeners



- Suitable for residential and commercial water softening applications, as coffee machines, dishwashers, microwave ovens;
- Tank in 304 Stainless Steel;
- They work with mains water pressure;
- They are supplied with and must be operated only with resin approved for drinking water contact use;
- For regeneration use only Sodium Chloride (NaCl) = coarse cooking salt.

Technical characteristics:

- Nominal Flow Rate at 4 bar = 1.000 l/h
- Operating Water Pressure Range: 1 ÷ 4 bar
- Feed Water Temperature Range: 4 ÷ 25°C
- Room Temperature Range: 4 ÷ 35° C
- Connections: 3/4" G (3/8" G reductions to order separately).

Ref	Description	Fam.	Subfam.		
ADD06	MWG MANUAL WATER SOFTENER 6 L	405	805		
ADD08	MWG MANUAL WATER SOFTENER 8 L	405	805		
ADD12	MWG MANUAL WATER SOFTENER 12 L	405	805		
ADD16	MWG MANUAL WATER SOFTENER 16 L	405	805		
ADD20	MWG MANUAL WATER SOFTENER 20 L	405	805		

Specific accessories

Ref.	Description	Fam.	Subfam.	
ADDR07	3/4" - 3/8" ADAPTER FOR MWG WATER SOFTENERS	405	806	

Ref	Box: WxLxH.	Box: Q.ty	Box: Weight.	Pallet: WxLxH.	Pallet: Q.ty	Pallet: Weight.
ADD06						
ADD08						
ADD12						
ADD16						
ADD20						

Certificates	Manufacturer	Sectors
DM174-2004	MWG	Domestic, Commercial