

Water softeners





RUNXIN Automatic Water Softeners GASTRO Series



- Suitable for residential water softening applications;
- With standard accessories and pre-assembled, with ion exchange resin;
- Standard colours: white tank and blue cover, in High Density Polyethylene (HDPE);
- With F79 Runxin Valve: electronic, volumetric, programmable, multilinguage.

- Pieces per 40' container = 1052.

| Ref. | Description | Fam. | Subfam. | |
|-------|--|------|---------|--|
| SR001 | GASTRO RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 7x13 |
| Resin Volume | 4 liters |
| Height | 510 mm |
| Width | 195 mm |
| Depth | 360 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 0,3 - 0,4 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 0,8 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkish, Catalan |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 240x410x550 | 1 | | | 24 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners GAIA-M Series



- Suitable for residential water softening applications;
 - With standard accessories and pre-assembled, with ion exchange resin;
 - Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
 - With F79 Runxin Valve: electronic, volumetric, programmable, multilinguage.
- Pieces per 40' container = 330.

| Ref. | Description | Fam. | Subfam. | |
|-------|--|------|---------|--|
| SR021 | GAIA-M RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 10x17 |
| Resin Volume | 12 liters |
| Height | 615 mm |
| Width | 326 mm |
| Depth | 525 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 1 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 2,5 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkisch, Catalan. |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 465x510x655 | 1 | | | 4 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners GAIA-XL Series



- Suitable for residential water softening applications;
- With standard accessories and pre-assembled, with ion exchange resin;
- Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
- With F79 Runxin Valve: electronic, volumetric, programmable, multilinguage.

- Pieces per 40' container = 220.

| Ref. | Description | Fam. | Subfam. | |
|-------|---|------|---------|--|
| SR041 | GAIA-XL RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 10x35 |
| Resin Volume | 25 liters |
| Height | 1070 mm |
| Width | 326 mm |
| Depth | 525 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 1,5 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 5,3 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkish, Catalan |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 465x510x1115 | 1 | | | 4 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners NIKE-M Series



- Suitable for residential water softening applications;
 - With standard accessories and pre-assembled, with ion exchange resin;
 - Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
 - With F79 Runxin Valve: electronic, volumetric, programmable, multilinguage.
- Pieces per 40' container = 315.

| Ref. | Description | Fam. | Subfam. |
|-------|--|------|---------|
| SR061 | NIKE-M RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 10x17 |
| Resin Volume | 12 liters |
| Height | 505 mm |
| Width | 350 mm |
| Depth | 580 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 1 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 2,5 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkish, Catalan |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 480x530x645 | 1 | | | 8 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners NIKE-XL Series



- Suitable for residential water softening applications;
 - With standard accessories and pre-assembled, with ion exchange resin;
 - Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
 - With F79 Runxin Valve: electronic, volumetric, programmable, multilingual.
- Pieces per 40' container = 210.

| Ref. | Description | Fam. | Subfam. | |
|-------|---|------|---------|--|
| SR081 | NIKE-XL RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 10x35 |
| Resin Volume | 25 liters |
| Height | 1050 mm |
| Width | 355 mm |
| Depth | 520 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 1,5 m3/h |
| Water capacity per cycle, specified for CaCO ₃ concentration 250 mg/l | 5,3 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkish, Catalan |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 480x530x1105 | 1 | | | 4 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners MARS-M Series



- Suitable for residential water softening applications;
- With standard accessories and pre-assembled, but without ion exchange resin;
- Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
- With F79 Runxin Valve: electronic, volumetric, programmable, multilinguage.

- Pieces per 40' container = 372.

| Ref. | Description | Fam. | Subfam. | |
|-------|--|------|---------|--|
| SR101 | MARS-M RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 9x17 |
| Resin Volume | 11 liters |
| Height | 598 mm |
| Width | 285 mm |
| Depth | 465 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 0,8 - 1 m3/h |
| Water capacity per cycle, specified for CaCO ₃ concentration 250 mg/l | 2,3 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkish, Catalan |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 385x515x655 | 1 | | | 8 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners MARS-L Series



- Suitable for residential water softening applications;
- With standard accessories and pre-assembled, with ion exchange resin;
- Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
- With F79 Runxin Valve: electronic, volumetric, programmable, multilinguage.

- Pieces per 40' container = 248.

| Ref. | Description | Fam. | Subfam. | |
|-------|--|------|---------|--|
| SR121 | MARS-L RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 9x35 |
| Resin Volume | 23 liters |
| Height | 1055 mm |
| Width | 285 mm |
| Depth | 485 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 0,8 - 1 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 4,8 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkish, Catalan. |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 385x515x1115 | 1 | | | 4 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners EOS-M Series



- Suitable for residential water softening applications;
 - With standard accessories and pre-assembled, with ion exchange resin;
 - Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
 - With F79 Runxin Valve: electronic, volumetric, programmable, multilinguage.
- Pieces per 40' container = 327.

| Ref. | Description | Fam. | Subfam. | |
|-------|---------------------------------------|------|---------|--|
| SR141 | EOS-M RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 10x17 |
| Resin Volume | 12 liters |
| Height | 615 mm |
| Width | 325 mm |
| Depth | 525 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 1 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 2,5 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkish, Catalan. |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 390x570x1135 | 1 | | | 8 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners EOS-XL Series



- Suitable for residential water softening applications;
 - With standard accessories and pre-assembled, with ion exchange resin;
 - Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
 - With F79 Runxin Valve: electronic, volumetric, programmable, multilinguage.
- Pieces per 40' container = 218.

| Ref. | Description | Fam. | Subfam. | |
|-------|--|------|---------|--|
| SR161 | EOS-XL RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 10x35 |
| Resin Volume | 25 liters |
| Height | 1070 mm |
| Width | 320 mm |
| Depth | 525 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 1,5 m3/h |
| Water capacity per cycle, specified for CaCO ₃ concentration 250 mg/l | 5,3 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkish, Catalan. |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 385x515x655 | 1 | | | 4 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners HERA-S Series



- Suitable for residential water softening applications;
 - With standard accessories and pre-assembled, with ion exchange resin;
 - Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
 - With F79 Runxin Valve: electronic, volumetric, programmable, multilinguage.
- Pieces per 40' container = 450.

| Ref. | Description | Fam. | Subfam. | |
|-------|--|------|---------|--|
| SR181 | HERA-S RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 8x17 |
| Resin Volume | 8 liters |
| Height | 630 mm |
| Width | 260 mm |
| Depth | 440 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 0,6 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 1,7 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkish, Catalan. |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 325x485x685 | 1 | | | 8 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners HERA-L Series



- Suitable for residential water softening applications;
 - With standard accessories and pre-assembled, with ion exchange resin;
 - Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
 - With F79 Runxin Valve: electronic, volumetric, programmable, multilingual.
- Pieces per 40' container = 300.

| Ref. | Description | Fam. | Subfam. | |
|-------|--|------|---------|--|
| SR201 | HERA-L RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 8x35 |
| Resin Volume | 20 liters |
| Height | 1090 mm |
| Width | 260 mm |
| Depth | 440 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 1,5 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 4,2 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkish, Catalan. |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 325x485x1150 | 1 | | | 4 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners SATURN-M Series



- Suitable for residential water softening applications;
 - With standard accessories and pre-assembled, with ion exchange resin;
 - Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
 - With F105 Runxin Valve: electronic, volumetric, programmable, multilinguage.
- Pieces per 40' container = 350.

| Ref. | Description | Fam. | Subfam. | |
|-------|--|------|---------|--|
| SR221 | SATURN-M RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 10x15 |
| Resin Volume | 11 liters |
| Height | 540 mm |
| Width | 315 mm |
| Depth | 450 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 1,5 - 4 bar |
| Suggested flow rate | 0,8 - 1 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 2,3 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Chinese. |
| Additional functions | With raw water pass valve during regeneration. Bypass included. With Hard-water mixing screw. Possibility to connect a disinfecting device. Anti-flooding protection. Vacation mode. Possibility to set the head in the closed position. Dry brine tank. Salt refill alarm. Service alarm. WIFI module. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 380x500x605 | 1 | | | 8 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners SATURN-XL Series



- Suitable for residential water softening applications;
- With standard accessories and pre-assembled, with ion exchange resin;
- Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
- With F105 Runxin Valve: electronic, volumetric, programmable, multilinguage.

- Pieces per 40' container = 250.

| Ref. | Description | Fam. | Subfam. | |
|-------|---|------|---------|--|
| SR241 | SATURN-XL RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|---|
| Connections In/Out | 3/4" |
| Resin Tank Size | 10x35 |
| Resin Volume | 25 liters |
| Height | 1045 mm |
| Width | 315 mm |
| Depth | 450 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 1,5 - 4 bar |
| Suggested flow rate | 1 - 2,5 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 5,3 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Chinese. |
| Additional functions | With raw water pass valve during regeneration. Bypass included. With Hard-water mixing screw. Possibility to connect a disinfecting device. Anti-flooding protection. Vacation mode. Possibility to set the head in the closed position. Dry brine tank. Salt refill alarm. Service alarm. WIFI module. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 380x500x1115 | 1 | | | 4 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners ROMA-M Series



- Suitable for residential water softening applications;
 - With standard accessories and pre-assembled, with ion exchange resin;
 - Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
 - With F79 Runxin Valve: electronic, volumetric, programmable, multilinguage.
- Pieces per 40' container = 350.

| Ref. | Description | Fam. | Subfam. | |
|-------|--|------|---------|--|
| SR261 | ROMA-M RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|--|
| Connections In/Out | 3/4" |
| Resin Tank Size | 10x15 |
| Resin Volume | 15 liters |
| Height | 545 mm |
| Width | 315 mm |
| Depth | 455 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 1,5 - 4 bar |
| Suggested flow rate | 0,8 - 1 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 2,3 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkisch, Catalan. |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. Possibility to connect a disinfecting device. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 380x500x605 | 1 | | | 8 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |

RUNXIN Automatic Water Softeners ROMA-XL Series



- Suitable for residential water softening applications;
 - With standard accessories and pre-assembled, with ion exchange resin;
 - Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
 - With F79 Runxin Valve: electronic, volumetric, programmable, multilingual.
- Pieces per 40' container = 250.

| Ref. | Description | Fam. | Subfam. | |
|-------|---|------|---------|--|
| SR281 | ROMA-XL RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|--|
| Connections In/Out | 3/4" |
| Resin Tank Size | 10x35 |
| Resin Volume | 25 liters |
| Height | 1050 mm |
| Width | 315 mm |
| Depth | 455 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 1,5 - 4 bar |
| Suggested flow rate | 1 - 2,5 m3/h |
| Water capacity per cycle, specified for CaCO ₃ concentration 250 mg/l | 5,3 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turkish, Catalan. |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. Possibility to connect a disinfecting device. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 380x500x1115 | 1 | | | 4 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



Automatic Water Softeners LUNA-XL Series



- Suitable for residential water softening applications;
 - With standard accessories and pre-assembled, with ion exchange resin;
 - Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
 - With F79 Runxin Valve: electronic, volumetric, programmable, multilinguage.
- Pieces per 40' container = 220.

| Ref. | Description | Fam. | Subfam. | |
|-------|---|------|---------|--|
| SR301 | LUNA-XL RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|--|
| Connections In/Out | 3/4" |
| Resin Tank Size | 10x35 |
| Resin Volume | 25 liters |
| Height | 1090 mm |
| Width | 360 mm |
| Depth | 490 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 1,5 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 7,3 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turckisch, Catalan. |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. Possibility to connect a disinfecting device. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 450x520x1135 | 1 | | | 4 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |



RUNXIN Automatic Water Softeners LUNA-XXL Series



- Suitable for residential water softening applications;
 - With standard accessories and pre-assembled, with ion exchange resin;
 - Standard colours: white tank and white cover, in High Density Polyethylene (HDPE);
 - With F79 Runxin Valve: electronic, volumetric, programmable, multilinguage.
- Pieces per 40' container = 110.

| Ref. | Description | Fam. | Subfam. | |
|-------|--|------|---------|--|
| SR321 | LUNA-XXL RUNXIN AUTOMATIC WATER SOFTENER | 405 | 807 | |

| Characteristics: | |
|--|--|
| Connections In/Out | 3/4" |
| Resin Tank Size | 10x44 |
| Resin Volume | 35 liters |
| Height | 1300 mm |
| Width | 360 mm |
| Depth | 490 mm |
| Power input | 100-240 V 50-60 Hz |
| Power output | 12 V 1,5 A |
| Maximum power | 18 W |
| Operating temperature | 5 - 38 °C |
| Operating pressure | 2 - 6 bar |
| Suggested flow rate | 1,5 m3/h |
| Water capacity per cycle, specified for CaCO3 concentration 250 mg/l | 7,4 m3 |
| Type of regeneration | Meter delayed UpFlow - Meter delayed DownFlow |
| Type of menu | Foreground menu (available for customer) - you can adjust water hardness. Background menu - you can adjust advanced settings. |
| Languages of menu | English, Spanish, French, Italian, German, Slovakian, Russian, Polish, Chinese, Turckisch, Catalan. |
| Additional functions | With raw water pass valve during regeneration. With External Bypass Valve. With Hard-water mixing screw. Possibility to connect a disinfecting device. |

| Box: WxLxH (mm) | Box: Q.ty | Box: Weight (kg) | Pallet: WxLxH (mm) | Pallet: Q.ty | Pallet: Weight (kg) |
|-----------------|-----------|------------------|--------------------|--------------|---------------------|
| 450x520x1400 | 1 | | | 4 | |

| Certificates | Manufacturer | Sectors |
|--------------|--------------|----------|
| CE | Runxin | Domestic |